PNEUMATIC MASTS (PIYUSH SERIES)



PEL's Piyush Series of Pneumatic Masts address the needs of Tactical Elevation for Radio Antenna, Electro-Optic, Anti-Drone and Illumination. These masts can be elevated by a Foot pump or Air compressor and support light, medium and heavy payloads. This series is capable of supporting up to 25 metres height and are easily mountable on vehicular shelters, trailers and ground.

OUR USP's



Quick Deployment by 2 person



Possibility for light weight solution



Precision

High stability and rigidity for Mission **Critical Applications**

Sailent Features

- Lightweight construction tubes in high strength Aluminum Alloy or Composite
- Telescopic mast sections extended by hand-pump, foot-pump OR compressor
- Full length key-ways ensure anti-rotation
- Heights up to 25 metres
- Top loads up to 250kg
- Several thousand in-service Masts with Security customers



Air Nozzle

Machanism

Types of Pneumatic Masts developed

Production Capacity per month





Base plate with Tilting Cup

Years of Experience

AS 9100D:2016 Quality certified ISO 9001:2015 manufacturing

PRECISION ELECTRONICS LIMITED

"we always know who we're working for"

contacts@pel-india.in +91-120-2551556 / 7 | Fax: +91-120-2524337 Released On. PEL 21052024-D Follow us on - in





TECHNICAL SPECIFICATIONS

		LIGHT DUTT FIM MASTS (GROUND / VEHICLE MOUNT)												
	Model No.	Height (m)		Head Load	Wind Area	Wind Speed (Operational/ Survival)	Sway	Weight of	No. of	Tube Dia	Ground Mount			
- 1	Model No.	Retracted	Erected	(Кд)	(m²)	(kmph)	(°)	Mast (Kg)	Sections	TUDE DIQ	No. of Guy Ropes	No. of Guy Ropes	Tripod Weight (kg)	
- 1	PP15P-5-1.7M-01	1.7	6	15	0.25	0.25	< 2	22	6	50 - 100	3 x 2	3 x 1	14	
	PP15P-9-2.5M-01	2.5	9	15	0.25	0.25	< 2	30	5	60 - 100	3 x 3	3 x 2	16	
- 1	PP10P-12-2.8M-01	2.8	12	10	0.2	0.2	< 2	37	6	50 - 100	3 x 3	3 x 2	18	
	PP15P-15-3.3M-01	3.3	15	15	0.25	0.25	< 2	47	6	60 - 110	3 x 4	3 x 3	20	

	Height	: (m)	Head Load	Wind Area (m²)	Wind Speed	Sway (°)	Weight of Mast (Kg)	No. of Sections	Tube Dia	No. of Guy Ropes		
Model No.	Retracted	Erected	(Kg)		(Operational/ Survival) (kmph)							
	MEDIUM DUTY PTM MASTS (GROUND / VEHICLE MOUNT)											
PP40P-12-2.8M-01	2.8	12	40	0.5	80/ 120	< 2	49	6	80 - 130	3 x 3		
PP30P-15-3.3M-01	3.3	15	30	0.4	80/ 120	< 2	53	6	70 - 120	3 x 4		
PP50P-18-3.6M-01	3.6	18	50	0.5	80/ 120	< 2	82	7	90 - 155	3 x 4		
	HEAVY DUTY PTM MASTS (GROUND / VEHICLE MOUNT)											
PP250P-5-1.2M-01	1.6	5	250	1	80/120	<]	46	5	130 - 183	3 x 4		
PP150P-10-2.2M-01	2.2	10	150	1	80/120	<]	90	7	130 - 214	3 x 4		
PP15P-22-3.7M-01	4	25	20	0.2	80/ 120	< 2	103	10	60 - 155	4 x 5		

Note:

a. Mast can be customized for wind load > 80 Km/Hr b. Accessories weight is applicable as per the height of the mast c. Mast sway < 1º can be provided against request

STANDARD ACCESSORIES & TOOL KIT





Pegs & Hammer | Base Plate & Nails | SS & Kevlar Guy ropes | Foot Pump | Tool kit

SPECIAL ACCESSORIES (OPTIONAL)



Vehicle Mounting Brackets



Air Compressor




Guy Rope Controller





Pneumatic Controller Unit











Adapter



Heavy Duty Payload

ANCILLARY

Payload



Dual Payload

Manual Rotator Tilter (MRT)



PSAP-50/100



Multi Function Active Junction Box

CARRYING CASES: SOFT/HARD





Rugged Case -Injection Moulding

PRECISION ELECTRONICS LIMITED



contacts@pel-india.in +91-120-2551556 / 7 | Fax: +91-120-2524337 Released On. PEL 21052024-D Follow us on - in



