



Precision

"We always know
who we're working for"

PRECISION ELECTRONICS LIMITED

Product Catalog

45

YEARS OF LEGACY

TABLE OF CONTENT

• Who We Are	...3	➤ Tripods	
• Certifications	...4	➤ LIGHT DUTY TRIPODS	...27
• Our Capabilities	...5	➤ MEDIUM DUTY TRIPODS	...29
• Our Products	...7	➤ ELEVATOR TRIPODS	...31
• Our Clients & Customers	...8	➤ HEAVY DUTY TRIPODS	...33
➤ Masts		➤ Positioners	
➤ PUSH-UP MASTS	...10	➤ SINGLE AXIS POSITIONERS	...36
➤ PNEUMATIC MASTS	...12	➤ DUAL AXIS POSITIONERS	...37
➤ WINCH MASTS	...14	➤ MANUAL ROTATOR/TILTER (MRT)	...38
➤ DETACHABLE SECTION BASED MASTS	...16	➤ Major Accessories	
➤ ELECTROMECHANICAL MASTS	...18	➤ MAST/TRIPOD/POSITIONER	...39
➤ VEHICULAR ROOFTOP MASTS	...20	➤ Multi Function Active Junction Box	...41
➤ BUILDING ROOFTOP TRIPOD MASTS	...22	➤ Power Solution	...42
➤ TACTICAL LIGHTING SYSTEM	...24		



WHO WE ARE

Precision Electronics Limited since its formation in 1979 has consistently delivered complex and highly reliable Products and Solutions. With a range spanning Tactical Infrastructure solutions including Telescopic Masts, Tripods & Pedestals; Power solutions for Telecom, Healthcare & Battery Electric Vehicles; and Box Build Manufacturing Services including Precision Machining, Sheet Metal, Electronic Assembly & System Assembly; PEL is honored to serve customers in Telecom, Hi-tech, Security, Government and Automotive.

100K+
PRODUCTS
DEPLOYED

40
PRODUCTS
DEVELOPED

45+
YEARS OF
LEGACY

100+
PROJECTS
EXECUTED

OUR CORE VALUES

At Precision Electronics Limited, we take great pride in offering high quality products and solutions with the highest degree of accuracy and quality standards to customers that demand it. We are committed to satisfy product RELIABILITY & AVAILABILITY and forge a partnership of TRUST with our customers.







Quality Certifications and Industry Standards Compliance



OUR CAPABILITIES



PRODUCTION CAPABILITIES

The production process at Precision Electronics Limited is characterized by meticulous attention to detail, stringent quality control measures, and a focus on efficiency and reliability. This is possible due to in-house State-of-the-art facilities for:

- Mechanical fabrication (CNC Turning, Milling)
- Mechanical Assembly (Welding, Drilling, Fastening, Shaping)
- Electronic Production (SMT pick & place, thru-hole)
- Wiring Harness
- Turnkey Box Build/ System Assembly & Testing

SECONDARY PROCESS CAPABILITIES

- Chromate conversion yellow / colorless as per MIL-DTL-5541F
- Electro-less Nickel (MIL-C-26074D)+ Electro-deposited Tin (MIL-T-10727C)
- Anodizing(MIL-A-8625): Hard and Regular
- Zinc Plating
- Black Oxide
- Passivation
- Powder coating
- PU Paint

VALIDATION CAPABILITIES

We undertake MIL-STD testing and ESS testing in-house to ensure product reliability and quality.



Dry Heat Chamber



Electro dynamic Vibration Machine



Salt Spray Chamber



Altitude Chamber



Hot and Cold Chamber



Thermal Shock Chamber

OUR PRODUCTS

We are a leading OEM engaged in the Design, Development, and Manufacturing of various Telescopic Masts, Tripods, Pedestals, and a wide range of Power Electronics and Data Interconnectivity solutions for Security, Telecom and Oil & Gas customers.

Telescopic Masts



Tripods



Positioners




Multi Function ACTIVE Junction Box



OUR CLIENTS & CUSTOMERS

Defence and Security



Civil Government

Telecom



Oil & GAS



Export



Indian Corporate



OUR MASTS

PEL provides a wide range of Telescopic Masts to suit every use case related to Line-Of-Sight for payloads ranging from Radio COMs, Radars, Electro-optics, Anti-Drone solutions, Lighting, etc. PEL's Mast portfolio encompasses all technologies including Pneumatic, Winch, Push-Up, Electro-Mechanical & Section based; and support mounting options for ground, building roof-tops and vehicles/trailers. Mast tubes are made from high strength aluminum alloy, FRP or carbon composites. PEL Masts cater demands of man portability, vehicle portability, quick deployment flexibility, high stability, MIL-STDs and various others.

➤ **ANJU SERIES**
Pushup Masts

➤ **SANJAY SERIES**
Electromechanical Masts

➤ **PIYUSH SERIES**
Pneumatic Masts


➤ **PARTHA SERIES**
Vehicular Rooftop Masts

➤ **YOGESH SERIES**
Winch Masts

➤ **PIYUSH SERIES**
Building Rooftop Tripod Masts

➤ **KAILASH SERIES**
Detachable Section Based Masts

➤ **Tactical Lighting System**



PUSH-UP MASTS

ANJU SERIES

PEL's Anju Series of Push up Masts are a portable mast that can be easily carried as manpack or loaded in the trunk of a small to mid-sized vehicle. It can be deployed using a light weight Tripod or as drive-on-frame system. Push up masts can be extended to a full height of 11 metres within a few minutes. It has quick lock/release collars to extend the mast manually by pushing up the sections and fixing them into position. Suitable for lightweight elevation requirements of smaller payloads such as cameras, lighting and radio antennae.

OUR USP'S



Designed for
MIL STDs



Man Portable



Quick Deployment
by 1 person



Maintenance
Free

Sailent Features

- Lightweight construction – tubes are made from high strength Aluminum Alloy
- Telescopic Mast sections manually "pushed up" with payload
- Quick locking mechanism to lock and release collars
- Heights up to 10 metres
- Top loads up to 10kg
- Can be stowed in trunk of small vehicle



Locking Pin



Tilting Adjustment



Locking Pin Pouch





DRIVE ON FRAME



TRIPOD MOUNT



PUSH-UP MASTS (DRIVE ON FRAME/ TRIPOD MAST)

Model No.	Height (m)		Head Load (kg)	Wind Area (m²)	Wind Speed (Operational/ Survival) (kmph)	Sway	Approx Weight of Mast (Kg)	No. of Sections	Tube Dia	No. of Guy Ropes	Weight (Kg)	
	Retracted	Erected									Frame	Tripod
PU10P-4-1.2M-30	1.2	4	10	0.1	60/80	<1°	8	5	50.8 - 76.2	-	10	5
PU8P-6-1.4M-30	1.4	6	8	0.1	60/80	<2°	10	6	44.45 - 76.2	-	11	6
PU5P-6-1.4M-30	1.6	6	5	0.1	60/80	<2°	12	6	44.45 - 76.2	3 x 1	12	7
PU5P-8-1.8M-01	1.8	8	5	0.1	80/100	<2°	13	8	31.8 - 76.2	3 x 2	-	8
PU5P-11-1.9M-01	1.9	11	5	0.1	80/100	<2°	14	8	31.8 - 76.2	3 x 2	-	9




Note:

- Built-to-Specifications available
- Comes in two configurations - either Drive-on-Frame or Tripod
- Guy ropes optional and typically needed for >6m erected height








ANCILLARY

-  Pan-Tilt (5kg)
-  Rotator (5kg)








SPECIAL ACCESSORIES

-  Payload Adapter
-  Earthing Kit: Pipe & Cable
-  Lightning Arrestor

STANDARD ACCESSORIES

-  Base Plate
-  Nails
-  Pegs
-  Hammer
-  Guy Rope
-  Carrying Cases: Soft/Hard
-  User Manual

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Velcro Cable Strap for Cable Tie
-  Levelor (Weighted Cable/ Spirit Level)
-  Guy Marker

PNEUMATIC MASTS


PIYUSH SERIES

PEL's Piyush Series of Pneumatic Masts address the needs of Tactical Elevation for Radio Antenna, Electro-Optic, Anti-Drone and Illumination. These masts can be elevated by a Foot pump or Air compressor and support light, medium and heavy payloads. This series is capable of supporting up to 25 metres height and are easily mountable on vehicular shelters, trailers and ground.

OUR USP'S



Designed for MIL STDs



Possibility for light weight solution




Quick Deployment by 2 person



High stability and rigidity for Mission Critical Applications

Sailent Features

- Lightweight construction – tubes in high strength Aluminum Alloy or Composite
- Telescopic mast sections extended by hand-pump, foot-pump OR compressor
- Full length key-ways ensure anti-rotation
- Heights up to 25 metres
- Top loads up to 250kg
- Several thousand in-service Masts with Security customers



Air Nozzle



Base plate with Tilting Cup



Locking Machanism



LIGHT DUTY PTM MASTS (GROUND / VEHICLE MOUNT)

Model No.	Height (m)		Head Load (Kg)	Wind Area (m²)	Wind Speed (Operational/ Survival) (kmph)	Sway (°)	Weight of Mast (kg)	No. of Sections	Tube Dia	Ground Mount	Tripod Mount	
	Retracted	Erected								No. of Guy Ropes	No. of Guy Ropes	Tripod Weight (kg)
PP15P-5-1.7M-01	1.7	6	15	0.25	0.25	< 2°	22	6	50 - 100	3 x 2	3 x 1	14
PP15P-9-2.5M-01	2.5	9	15	0.25	0.25	< 2°	30	5	60 - 100	3 x 3	3 x 2	16
PP10P-12-2.8M-01	2.8	12	10	0.2	0.2	< 2°	37	6	50 - 100	3 x 3	3 x 2	18
PP15P-15-3.3M-01	3.3	15	15	0.25	0.25	< 2°	47	6	60 - 110	3 x 4	3 x 3	20

Model No.	Height (m)		Head Load (kg)	Wind Area (m²)	Wind Speed (Operational/ Survival) (kmph)	Sway (°)	Weight of Mast (kg)	No. of Sections	Tube Dia	No. of Guy Ropes
	Retracted	Erected								

MEDIUM DUTY PTM MASTS (GROUND / VEHICLE MOUNT)

PP40P-12-2.8M-01	2.8	12	40	0.5	80/ 120	< 2°	49	6	80 - 130	3 x 3
PP30P-15-3.3M-01	3.3	15	30	0.4	80/ 120	< 2°	53	6	70 - 120	3 x 4
PP50P-18-3.6M-01	3.6	18	50	0.5	80/ 120	< 2°	82	7	90 - 155	3 x 4





HEAVY DUTY PTM MASTS (GROUND / VEHICLE MOUNT)

PP250P-5-1.2M-01	1.6	5	250	1	80/ 120	< 1°	46	5	130 - 183	3 x 4
PP150P-10-2.2M-01	2.2	10	150	1	80/ 120	< 1°	90	7	130 - 214	3 x 4
PP15P-22-3.7M-01	4	25	20	0.2	80/ 120	< 2°	103	10	60 - 155	4 x 5









Note:

- a. Mast can be customized for wind load > 80 Km/Hr
 b. Accessories weight is applicable as per the height of the mast
 c. Mast sway < 1° can be provided against request











ANCILLARY

-  Manual Rotator Tilter (MRT)
-  Pan-Tilt (25/ 50kg)
-  Rotator (50/ 100kg)
-  Multi Function Active Junction Box











SPECIAL ACCESSORIES

-  Payload Adapter
-  Vehicle Mounting Brackets
-  Earthing Kit: Pipe & Cable
-  Lightning Arrestor
-  Pneumatic Controller Unit
-  Air Compressor (Optional)
-  Guy Rope Controller
-  Sand Kit

STANDARD ACCESSORIES

-  Base Plate
-  Tilting Cup
-  Nails
-  Pegs
-  Hammer
-  Guy Rope
-  Foot Pump
-  Erection Stand
-  Carrying Cases: Soft/Hard
-  User Manual

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Velcro Cable Strap for Cable Tie
-  Levelor (Weighted Cable/ Spirit Level)
-  Box Spanner with T Handle
-  Teflon Tape
-  Steel Oil Can
-  Guy Marker

WINCH MASTS

YOGESH SERIES

PEL's Yogesh Series of Winch Masts cater to the requirements of Tactical Elevation for applications such as Radio Antenna, Electro-Optic, Anti-Drone and Illumination. These masts can be raised using either a hand crank or a winch power drive, and they are capable of supporting light, medium, and heavy payloads up to 21 metres. Additionally, they can be conveniently mounted on vehicular shelters, trailers and ground.

OUR USP'S



Designed for MIL STDs



Capable of extreme temperature operations




Quick Deployment by 2 person



High stability and rigidity for Mission Critical Applications

Silent Features

- Lightweight construction – tubes in high strength Aluminum Alloy or Composite
- Telescopic mast sections extended simultaneously by high performance belts
- Full length key-ways ensure anti-rotation
- Heights up to 18 metres
- Top loads up to 100kg
- Hand cranked manual or electrically driven winch
- Several hundred in-service Masts with Security customers



Pulley Drive



Winch



Locking Plate



WINCH MASTS (GROUND / VEHICLE MOUNT)

HAND WINCH MASTS

Model No.	Height (m)		Head Load (Kg)	Wind Area (m ²)	Wind Speed (Operational/ Survival) (kmph)	Sway (°)	Weight of Mast (Kg)	No. of Sections	Tube Dia	No. of Guy Ropes	Winch Weight (Kg)
	Retracted	Erected									
PW100P-9-3M-01	3	9	100	1	80/ 120	< 1°	50	4	100 - 214	3 x 3	8
PW70P-10-2.5M-01	2.5	10	70	0.75	80/ 120	< 1°	65	6	100 - 155	3 x 4	8
PW50P-15-2.8M-01	3	15	50	0.5	80/ 120	< 1°	84	7	90 - 155	3 x 5	8
PW50P-18-3M-01	3	18	50	0.7	80/ 120	< 1°	132	9	100 - 198	3 x 3	8
PW40P-2-1.5M-20	1.5	2	40	0.7	80/ 120	< 1°	15	2	70 - 80	-	8
PW65P-5-2M-20	2	5	65	0.8	80/ 120	< 1°	66	4	120 - 155	-	8

ELECTRICAL WINCH MASTS

Model No.	Height (m)		Head Load (Kg)	Wind Area (m ²)	Wind Speed (Operational/ Survival) (kmph)	Sway (°)	Weight of Mast (Kg)	No. of Sections	Tube Dia	No. of Guy Ropes	EM Unit Weight(Kg)
	Retracted	Erected									
PE70P-10-2.5M-01	2.5	10	70	0.75	80/ 120	< 1°	65	6	100 - 155	3 x 3	25
PE50P-15-2.8M-01	3	15	50	0.5	80/ 120	< 1°	84	7	90 - 155	3 x 4	25
PE50P-18-3M-01	3	18	50	0.7	80/ 120	< 1°	132	9	100 - 198	3 x 5	25
PE50P-21-3M-01	3	21	50	0.6	80/ 120	< 1°	165	10	100 - 214	3 x 5	25

Note:

- a. External winch Power Drive is available as an option
b. Mast can be customized for wind load > 80 Km/Hr

ANCILLARY

- Manual Rotator Tilter (MRT)
- Pan-Tilt (25/ 50kg)
- Rotator (25/ 50/ 100kg)
- Multi Function Active Junction Box

SPECIAL ACCESSORIES

- Payload Adapter
- Vehicle Mounting Brackets
- Earthing Kit: Pipe & Cable
- Lightning Arrestor
- Sand Kit
- Hand Held Pendant

STANDARD ACCESSORIES

- Base Plate
- Tilting Cup
- Nails
- Pegs
- Hammer
- Guy Rope
- Erection Stand
- Carrying Cases: Soft/Hard
- User Manual

TOOL KIT

- DE Spanner
- Adjustable Spanner
- Screw Driver
- Allen Keys
- Steel Oil Can
- Velcro Cable Strap for Cable Tie
- Box Spanner with T Handle
- Guy Marker

DETACHABLE SECTION MASTS

KAILASH SERIES

PEL's Kailash Series of Detachable Section Masts are an ideal solution to cater Tactical Elevation requirements in conditions where Man-portability is also desired. The solution comprises a Tripod and Pipe sections of the same length and diameter which are "pushed up" from the Tripod via a hand winch mechanism. The mast is stabilized using guy ropes and a guy cable ensures that no more than 2 persons are needed for Mast deployment. This series is capable of supporting up to 18 metres height.

OUR USP'S



Designed for MIL STDs



Man Portable



Possibility for light weight solution




High stability and rigidity for Mission Critical Applications

Sailent Features

- Lightweight construction – tubes in high strength Aluminum Alloy or Composite
- Tripod base with sectional tubes of same height and diameter are pushed-up via hand-winch mechanism
- Built-in anti-rotation
- Heights up to 18 metres
- Top loads up to 50kg
- Hand cranked manual winch
- Guy Rope Controller ensures safe deployment and reduces man-power required
- Integrated spirit level on Tripod to enable flatness on uneven ground



Tripod



Mast Sections



Winch





DETACHABLE SECTION BASED HAND WINCH OPERATED TRIPOD MASTS

Model No.	Height (m)		Head Load (kg)	Wind Area (m²)	Wind Speed (Operational/ Survival) (kmph)	Sway (°)	Approx. Weight of Sections & Tripod (kg)	No. of Sections	Tube Dia	No. of Guy Ropes
	Section	Erected								
PD20P-10-1.4M-21	1.4	10	20	0.25	80/120	<2°	37	7 + 1	60	3 x 3
PD40P-18-2.0M-21	2	18	40	0.5	80/120	<2°	120	13 + 1	120	3 x 4

Note:

a. Specifications are subject to change without notice

ANCILLARY

- Manual Rotator Tilter (MRT)
- Pan-Tilt (25kg)
- Multi Function Active Junction Box

SPECIAL ACCESSORIES

- Payload Adapter
- Earthing Kit: Pipe & Cable
- Lightning Arrestor
- Sand Kit
- Guy Rope Controller

STANDARD ACCESSORIES

- Base Plate
- Nails
- Pegs
- Hammer
- Guy Rope
- Carrying Cases: Soft/Hard
- User Manual

TOOL KIT

- DE Spanner
- Adjustable Spanner
- Screw Driver
- Allen Keys
- Velcro Cable Strap for Cable Tie
- Levelor (Weighted Cable/ Spirit Level)
- Box Spanner with T Handle)
- Guy Marker

ELECTROMECHANICAL MASTS


SANJAY SERIES

PEL's Sanjay Series of Heavy Duty Electro-mechanical Telescopic masts are self supported, vehicle mounted masts. The masts are elevated/ retracted by a Lead Screw (Spindle) which in turn is powered by an electric motor. Ideally suited to lift multiple payloads requiring tactical elevation from a vehicular platform.

OUR USP'S



Designed for MIL STDs



Remote Control
Elevation &
Retraction




Suitable for
On-the-Quick-Halt
vehicular operations




High stability and
rigidity for Mission
Critical Applications

Sailent Features

- Heavy duty construction – tubes in high strength Aluminum Alloy
- Telescopic mast sections extended by screw drive and high performance belts Suitable for deployment on vehicles, shelters or trailers
- Full length key-ways ensure anti-rotation
- Heights up to 12 metres
- Top loads up to 350kg
- Push-button motorized deployment in tactical time frames
- Excellent solution for On the Quick Halt applications
- Suitable for deployment on vehicles, shelters or trailers



Control Box



Mast Sections



Motor Assembly

ELECTROMECHANICAL MASTS (HYBRID SPINDLE)




Model No.	Height (m)		Head Load (kg)	Wind Area (m ²)	Wind Speed (Operational/ Survival) (kmph)	Sway	Weight of Mast (kg)	No. of Sections	Tube Dia
	Retracted	Erected							
PH350P-6.5-1.6M-10	1.6	6.5	350	1	80/ 100	< 1°	160	7	130 – 214
PH214-8-1.6M-10	1.6	8	150	1	80/ 100	< 1°	165	9	110 – 214
PH214-8-2.1M-10	2.1	8	150	1	80/ 100	< 1°	160	7	120 – 198
PH214-10-2.3M-10	2.3	10	150	1	80/ 100	< 2°	180	7	120 – 198
PH214-12-2.3M-10	2.3	12	150	1	80/ 100	< 2°	200	8	120 – 214

Note:




- a.Mast can be customized for higher wind load > 80 Km/Hr
- b.Mast with Sway < 1° can be provided upon request
- c.Option for DC Motor is available

S.No.	PARAMETER	SPECIFICATIONS
1	Operating Voltage	230V/50Hz
2	Drive	Single or Three Phase AC Motor
3	Operation	Control Panel and Pendant
4	Operational(Temp)	-20°C to +60°C
5	Environmental	MIL STD 810 F/G



ANCILLARY

-  Pan-Tilt (50kg)
-  Rotator (50/ 100kg)
-  Multi Function Active Junction Box

SPECIAL ACCESSORIES

-  Payload Adapter
-  Vehicle Mounting Brackets
-  Earthing Kit: Pipe & Cable

STANDARD ACCESSORIES

-  Hand Held Pendant
-  User Manual

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Steel Oil Can
-  Velcro Cable Strap for Cable Tie
-  Levelor (Weighted Cable/ Spirit Level)
-  Box Spanner with T Handle

VEHICULAR ROOF TOP MASTS

PARTHA SERIES

PEL's Vehicular Roof Top Masts are specially designed for mid-sized and larger vehicles to support payloads such as Electro-Optics, Radio antennae, Illumination systems, and others. It easily mounts as a roof top carrier and does not require the end-user to make vehicle modifications for its use.

OUR USP'S



Designed for MIL STDs



Suitable for On-the-Quick-Halt vehicular operations



Remote Operation from Cabin




Quick deployment

Silent Features

- Compact, roof-mount system on vehicle carrier
- Integrated air compressor and Li-Ion battery for mast lift/ retraction and power supply
- Built-in anti-rotation
- Wide range of payload capacity and height options from 3 metres to 5 metres above Roof Top
- Top loads up to 50kg
- Handheld Pendant for remote operation of mast and payload Pan / Tilt



Pneumatic Mast Section



Roof Top Mast System



Vehicle Roof Mount Design







VEHICLE ROOF TOP MASTS

Model No.	Height (m)		Head Load (kg)	Wind Area (m²)	Wind Speed (Operational/ Survival) (kmph)	Sway	Weight of Mast (kg)	No. of Sections	Tube Dia (mm)	Power Backup*	Power*	Dimensions (mm)	Mounting Frame Base (mm)
	Retracted	Erected											
PRT30P-3-1.2M	1.2	3	30	0.2	80/ 120	< 2°	55	4	70-100	5- 6 Hrs	12 /24 V 120W	1200 (L) x 700 (W) x 400 (H)	700 (W) x 1200 (L)
PRT50P-3-1.2M	1.2	3	50	0.3	80/ 120	< 2°	65	4	90-120	4-5 Hrs	12 /24 V 150W	1400 (L) x 800 (W) x 400 (H)	800 (W) x 1400 (L)




Note:

- a. Mast can be customized for higher Wind load > 80 Km/Hr
- b. Accessories weight is applicable as per the height of the mast.

STANDARD ACCESSORIES

-  Hand Held Pendant
-  Pegs
-  Hammer
-  Guy Rope
-  User Manual

SPECIAL ACCESSORIES

-  Payload Adapter
-  Earthing Kit: Pipe & Cable
-  Lightning Arrestor

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Steel Oil Can
-  Velcro Cable Strap for Cable Tie
-  Box Spanner with T Handle

BUILDING ROOFTOP TRIPOD MASTS

PIYUSH SERIES

PEL's Building Rooftop Masts are a unique solution to deploy complex electronics such as base station RF front end and antenna of DMR/ TETRA/ LoRA/ LTE/ 5G cellular, Anti-Drone and other such systems required to provide communications in dense urban settings or secure critical infrastructure. These masts can be elevated by Air compressor and support medium and heavy payloads. Such masts are capable of supporting up to 10m height and up to 250kg payload. Their key advantage is that they can be lowered for any maintenance or repair of the payload and are much lighter and safer than equivalent fixed rooftop Towers and Masts.

OUR USP'S



Designed for MIL STDs



Possibility for light weight solution



Technician friendly and safe




High stability and rigidity for Mission Critical Applications

Sailent Features

- Lightweight construction – tubes in high strength Aluminum Alloy or Composite
- Telescopic mast sections extended by compressor
- Full length key-ways ensure anti-rotation
- Heights up to 10 metres
- Top loads up to 250kg
- Specialized Tripod design for installation on building Rooftops
- Provides very safe approach of lowering payload for Maintenance purposes
- Can be fixed on Concreate plinth
- Provision of putting Dead Weight (Sand Bag) on its base for temporary Deployment.



Hole for Concrete Anchor Bolts



Foot



Base plate





BUILDING ROOFTOP TRIPOD MASTS

Model No.	Height (m)		Head Load (Kg)	Wind Area (m²)	Wind Speed (Operational/ Survival) (kmph)	Sway	Weight of Mast (Kg)	No. of Sections	Tube Dia (mm)	No. of Guy Ropes
	Retracted	Erected								
PP250P-5-1.2M-01	1.6	5	250	1	80/ 120	< 1°	46	5	130 - 183	3 x 4
PP150P-10-2.2M-01	2.2	10	150	1	80/ 120	< 1°	90	7	130 - 214	3 x 4







Note:

- a. Mast can be customized for wind load > 80 Km/Hr
- b. Accessories weight is applicable as per the height of the mast
- c. Mast sway < 1° can be provided against request








ANCILLARY

-  Rotator (100kg)
-  Multi Function Active Junction Box

SPECIAL ACCESSORIES

-  Payload Adapter
-  Earthing Kit: Pipe & Cable
-  Lightning Arrestor
-  Sand Kit
-  Guy Rope Controller
-  Air Compressor (Optional)

STANDARD ACCESSORIES

-  Base Plate
-  Nails
-  Pegs
-  Hammer
-  Guy Rope
-  Carrying Cases: Soft/Hard
-  User Manual

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Velcro Cable Strap for Cable Tie
-  Levelor (Weighted Cable/ Spirit Level)
-  Box Spanner with T Handle
-  Teflon Tape
-  Steel Oil Can
-  Guy Marker

TACTICAL LIGHTING SYSTEM

PEL's Tactical Lighting System is meant to cater requirements of Tactical Illumination for Military bases & Field HQs, Border Forces, Critical Infrastructures and Strategic Construction sites. The Lighting System can be powered either by Generator, inverter or commercial electric power. The system caters from 60° to 360° coverage.

Tripod based Pneumatic Mast is extended by air pressure from the Hand Air Pump. Option for Winch Mast also available.

The light fixtures can be controlled (i.e. ON-OFF, Dimmer) by an App on a Smart Phone or via the Junction Box/ PDU available at Tripod base.

OUR USP'S



Designed and Qualified for MIL STD.



Suitable for On-the-Quick-Halt vehicular operations



Maintenance Free for 800 Lifts / 2 Years Operation



High stability and rigidity for Mission Critical Applications



Remote operation using mobile phone

Silent Features

- Quick & Simple Installation of Tripod mast light fixture
- The tripod has adjustable legs which help to erect the mast on uneven ground
- The mast and tripod are made of lightweight aluminium alloy tubes, enables frequent erections and retractions without damage
- Option for Remote switch ON and OFF from Mobile Phone
- Additional safety by using additional weights at high wind speed
- Surge protection for incoming Power supply
- Each light is connected to junction box with quick latch plug and can be replaced if required



Light Controller

MAST MECHANICAL PARAMETERS /SPECIFICATIONS






S.No.	Parameters	Specifications
1	Type of Mast	Pneumatic – Tripod – Un-Guyed
2	Extended height	Up to 5 Meters (Min.)
3	Folded height	< 1.5 Meters
4	Maximum spread -legs	2.0 Mtr
5	Head Load capacity	40 Kgs (Max.)
6	Wind Area of Payload	0.4 M²
7	Operational – Wind Speed	60 Kmph
8	Survival – Wind Speed	80 Kmph
9	Pipe's Material	Al. Alloy – 6063 T6
10	Application	Tripod Mount – Un-guyed
11	Installation	Ground Mount
12	Type of Operation	Pneumatic – Hand Air Pump
13	Weight of mast with Tripod	< 30 Kg
14	Weight of Mast Accessories	< 10 Kg
15	The weight of the complete lighting fixture	~35 kg (with junction box)
16	Environmental specs	MIL-STD 810F /JSS55555
17	Quantity of modules	Up to 6 modules
18	Light power Consumption	167 W each (Total >1000W)
19	a. Total light power in LUMAN at Level 0	>25000 lm (each Light module) Total 1,50,000 lm
20	The lighting fixtures Power input	Voltage: 230VAC Freq 50 HZ
21	The lighting module illumination	Up to 360 degrees
22	Coverage Area	Up to 100 Mtrs (Subjected to Mast height and light selection)
23	Sway	< 2°
24	Operating Temperature	- 10°C to + 55°C
25	Storage Temperature	- 20°C to + 70°C

Note: a. Specifications are subject to change without prior notice











Packing Details of Tactical Light system

S.No.	
1	Tripod Mast with accessories
2	Light fixture fitted with Junction Box
3	Power distribution Box with Power cables
4	Hard/ soft carrying case








SPECIAL ACCESSORIES

-  Payload Adapter
-  Earthing Kit: Pipe & Cable
-  Lightning Arrestor
-  Sand Kit
-  Air Compressor (Optional)

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Velcro Cable Strap for Cable Tie
-  Levelor (Weighted Cable/ Spirit Level)
-  Box Spanner with T Handle
-  Teflon Tape
-  Steel Oil Can
-  Guy Marker

STANDARD ACCESSORIES

-  Base Plate
-  Nails
-  Pegs
-  Hammer
-  Guy Rope
-  Carrying Cases: Soft/Hard
-  User Manual

OUR TRIPODS

PEL has a wide range of Tripods together with passive and active accessories that support Industrial and Defence customers. The Tripods are constructed with options of high strength Aluminum Alloy or FRP/ Carbon composites. When your application demands critical stability, performance in extreme conditions and a product to suit mostly any use case, look no further than the Pankh, Haldar, Sudesh and Balwan series of PEL Tripods.

➤ PANKH SERIES

Light Duty Tripods

➤ HALDAR SERIES

Medium Duty Tripods

➤ SUDESH SERIES

Tripod with Elevators

➤ BALWAN SERIES

Heavy Duty Tripods

Medium Duty Tripod



Light Duty Tripod



Tripod with Elevator

Heavy Duty Tripod



LIGHT DUTY TRIPODS

PANKH SERIES

PEL's Pankh Series of Light Duty Tripods provide ultimate portability—weighing in at under 5kg, it's effortlessly man-portable and conveniently packed in a soft or hard carry case.

OUR USP'S



Designed and Qualified for MIL STD



Mounting Flexibility for any Ground Surface



Excellent Portability



Quick Deployable

Silent Features

- Ultra-light, robust and compact design
- Simple installation and operation
- Hard Anodized coating
- High Torsional rigidity
- Maximum height up to 3 metres
- Maximum payload capacity up to 5 kg
- Material: High strength Aluminum alloy
- Small stowed size and packed in soft carrying case



Tripod Adjustment



Hole for Nail Grouting



Stowed



LIGHT DUTY TRIPODS							
Model No.	Height (m)		Head Load (kg)	Weight of Tripod (kg)	Max Spread dia (mm)	Accessories weight (kg)	Folding Dimensions (mm)
	Retracted	Erected					
PTU10P-1.5-1.1M	1100	1500	10	3.5	1010	2	925 (L) x 190 (W) x 75 (H)
PTU3P-3.0-1.2M	1200	3000	3	5.5	1250	2	925 (L) x 190 (W) x 95 (H)

Note: Customized for greater heights and peculiar payloads against request

STANDARD ACCESSORIES

- Nails
- Hammer
- Carrying Cases: Soft/Hard
- User Manual

TOOL KIT

- Nail Puller

MEDIUM DUTY TRIPODS

HALDAR SERIES

PEL's Haldar Series of Medium Duty Tripods has been developed for customers with medium duty payloads up to 70 kg with an economical design, well suited for direct mounting of payloads on its top plate. These Tripods are easy to use, rugged design, man- portable, flexible to deploy and highly stable for payloads. PEL offers several options of foot plates to suit various ground surfaces.

OUR USP'S



Designed for
MIL STD



Mounting
Flexibility for any
Ground Surface



Excellent
Portability



Highly stable for
Payloads



Quick
Deployable

Silent Features

- Light, rugged and ideally suited for professional payloads up to 100kg
- Easily Deployable in tough field conditions
- Hard Anodized coating
- High Torsional rigidity ideal for rotating payloads
- Max Height 1.5 Metres
- Maximum Payload up to 70 Kg
- Material: High strength Aluminum alloy
- Powder Coated and Hard anodized parts for extreme environments
- Foot plates for hard, semi-hard and soft ground surfaces



Levler



Stabilizer






Foot





MEDIUM DUTY TRIPODS							
Model No.	Height (m)		Head Load (kg)	Weight of Tripod (kg)	Max Spread dia (mm)	Accessories weight (kg)	Folding Dimensions (mm)
	Retracted	Erected					
PT70P-1.5-1.1M	1100	1500	70	14	1850	5	360 x 1350 (L)
PT55P-1.5-1.1M	1100	1500	55	12.5	1850	5	360 x 1350 (L)

Note: Customized for greater heights and peculiar payloads against request

ANCILLARY

-  Pan-Tilt (25kg)
-  Rotator (50kg)
-  Multi Function Active Junction Box







SPECIAL ACCESSORIES

-  Payload Adapter
-  Earthing Kit: Pipe & Cable

STANDARD ACCESSORIES

-  Nails
-  Hammer
-  Carrying Cases: Soft/Hard
-  User Manual

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Velcro Cable Strap for Cable Tie
-  Nail Puller

ELEVATOR TRIPODS

SUDESH SERIES

PEL's Sudesh Series of Tripods have been developed for customers that seek compact stowed dimensions and better elevation (height) for medium duty payloads up to 100kg. These Tripods are easy to use, rugged design, man- portable, flexible to deploy and highly stable for payloads such as Radio COMs, Radars, Electro-optics, Anti-Drone, etc. The system comes with a manual Elevation mechanism for the payload height.

OUR USP'S



Designed for
MIL STD



Mounting
Flexibility for any
Ground Surface



Excellent
Portability




Highly stable
for Payloads



Quick
Deployable

Sailent Features

- Robust, portable and highly stable Tripod
- Easily Deployable in tough field conditions
- Hard Anodized coating
- High Torsional rigidity
- Maximum height up to 1.8 metres
- Maximum Payload up to 100 kg
- Material: High strength aluminum alloy
- Powder coated and Hard anodized parts for extreme conditions
- Footplates for hard, semi-hard and soft surfaces



Winch



Stabilizer



Foot



MEDIUM DUTY ELEVATOR TRIPODS							
Model No.	Height (m)		Head Load (kg)	Weight of Tripod (kg)	Max Spread dia (mm)	Accessories weight (kg)	Folding Dimensions (mm)
	Retracted	Erected					
PTE70P-1.8-0.8M	850	1800	70	18	2100	5	360 x 1080 (L)
PTE100P-1.8-0.8M	870	1800	100	19	2100	5	360 x 1100 (L)

Note: Customized for greater heights and peculiar payloads against request

ANCILLARY

- Pan-Tilt (25/ 50kg)
- Rotator (50/ 100kg)
- Multi Function Active Junction Box

SPECIAL ACCESSORIES

- Payload Adapter
- Earthing Kit: Pipe & Cable

STANDARD ACCESSORIES

- Nails
- Hammer
- Carrying Cases: Soft/Hard
- User Manual

TOOL KIT

- DE Spanner
- Adjustable Spanner
- Screw Driver
- Allen Keys
- Velcro Cable Strap for Cable Tie
- Nail Puller

HEAVY DUTY TRIPODS

BALWAN SERIES

PEL Balwan Series of Heavy Duty Tripods provide very high stability for payloads such as Radars, Electro-Optic Sensors and Anti-Drone systems. High strength Aluminum alloy based design ensures reliability and economy of weight. Packed in a convenient carrying case, it's quick deployable for on-the-go missions.

OUR USP'S



Designed for MIL STD



Mounting Flexibility for any Ground Surface



Excellent Portability



Highly stable for Payloads



Quick Deployable

Silent Features

- Professional tripod for Heavy duty payloads
- Easily Deployable in tough field conditions
- Hard Anodized coating
- Strong Tubular Construction with high torsional rigidity
- Max Height 1.5 Metres
- Maximum Payload up to 400 Kg
- Material: High strength aluminum alloy
- Powder coated and Hard anodized parts for extreme conditions
- Footplates for hard, semi-hard and soft ground




Leveler



Stabilizer






Foot





HEAVY DUTY TRIPODS							
Model No.	Height (m)		Head Load (kg)	Weight of Tripod (kg)	Max Spread dia (mm)	Accessories weight (kg)	Folding Dimensions (mm)
	Retracted	Erected					
PT100P-1.5-1.1M	1100	1500	100	16	2000	5	360 x 1350 (L)
PT100P-1.5-1.1M	1100	1500	200	19	2100	5	360 x 1350 (L)
PT400P-1.5-1.1M	1100	1500	400	26	2100	6	480 x 1400 (L)

Note: Customized for greater heights and peculiar payloads against request


ANCILLARY

-  Pan-Tilt (25/ 50kg)
-  Rotator (50/ 100kg)
-  Multi Function Active Junction Box







SPECIAL ACCESSORIES

-  Payload Adapter
-  Earthing Kit: Pipe & Cable

STANDARD ACCESSORIES

-  Nails
-  Hammer
-  Carrying Cases: Soft/Hard
-  User Manual

TOOL KIT

-  DE Spanner
-  Adjustable Spanner
-  Screw Driver
-  Allen Keys
-  Velcro Cable Strap for Cable Tie
-  Nail Puller

"We always know who we're working for"



POSITIONERS

PEL delivers Precise Positioning with its family of Single and Dual-Axis Positioners to accurately align, point or track Radio Antenna, Electro-Optic systems, Anti-Drone systems or Search Lighting systems. PEL Positioners can be guided manually; semi-auto or fully automatically by specialized control algorithms that depend on GNSS, RF Signal Strength and/or an external C2 system.

➤ EKLAVYA SERIES

Single Axis positioners

➤ ARJUN SERIES

Dual Axis positioners

➤ NAKUL SERIES

Manual Rotator/Tilter (MRT)





SINGLE AXIS POSITIONERS

EKLAVYA SERIES

PEL's Eklavya Series of Single-axis positioners are specifically engineered to achieve precise azimuth positioning. They provide the option for continuous rotation (360 degrees) or +/- 180 degrees, catering to various payloads such as radio antennas, electro-optic systems, C-UAS systems, etc. The Rotator can be mounted on a portable Tripod, Telescopic Mast or on a fixed structure.

OUR USP'S




Built-in Controller provides smooth and precise motion at all speeds



Rugged, compact and low weight construction



Continuous rotation via slip ring



High accuracy, high speed (up to 180 deg/sec)

SINGLE AXIS POSITIONERS (PEDESTALS)									
Model No.	Payload (kg)	Unit Wt (kg)	Dimensions (mm)	Power Consumption	Rotational Range	Positional Accuracy	Rotational speed (RPM)	Control Data Interface	Wind Area (m²)
PSAP-5	5	~ 5	180 x 144 x 220 (LXWXH)	24V DC 30 W Nominal	Continuous 360° Sector scan ± 180°	0.1°	1 to 20 RPM	RS422 (Ethernet Optional)	0.2
PSAP-30	35	~ 14	377 x 310 x 300 (LXWXH)	18-36V DC 80W Nominal	Continuous 360° Sector scan ± 180°	0.1°	1 to 20 RPM	RS422 (Ethernet Optional)	0.3
PSAP-50	60	~ 14	245 Dia x 235 Height	18-36V DC 200 W Nominal	Continuous 360° Sector scan ± 180°	0.1° (0.05° Optional)	1 to 30 RPM	RS422 and Ethernet	0.8
PSAP-100	125	~ 22	360 Dia x 265 Height	18-36V DC 350 W Nominal	Continuous 360° Sector scan ± 180°	0.1° (0.05° Optional)	1 to 30 RPM	RS422 and Ethernet	0.8

STANDARD ACCESSORIES



Hard carrying case



Set of Cables

SPECIAL ACCESSORIES



Payload



Bracket/Adaptor

DUAL AXIS POSITIONERS

ARJUN SERIES

PEL's Arjun Series of Dual-Axis positioners provides accurate alignment for Radio Antenna, electro-optic systems, C-UAS systems, etc. A precision machined aluminum alloy enclosure contains a rotating base with an elevation arm and built-in controller. It can be guided manually, semi-automatically or fully automatically. The Pan-Tilt system can be mounted on a portable Tripod, Telescopic Mast or on a fixed structure.

OUR USP'S



Rugged, compact and high reliability construction



Built-in Controller provides smooth and precise motion at all speeds



Auto tracking via Special Control algorithms



High degree of customizations available

DUAL AXIS POSITIONERS (PEDESTALS)

Model No.	Payload (Kg)	Unit Wt (Kg)	Dimensions (mm)	Power Consumption	Rotational Range	Tilt Range	Positional Accuracy	Speed (RPM)	Control Data Interface	Wind Area (m ²)
PDAP-5	5	~ 6	245 x 220 x 144 (W x H x D)	24V DC 30 W Nominal	"Sector scan $\pm 180^\circ$ " Continuous 360° (optional)*	(-90) to (+35)	0.1"	Azimuth: 1 to 20 Elevation 1 to 10	RS422 (Ethernet-Optional)	0.2
PDAP-25	25	~ 16	335 x 266 x 370 (W x H x D)	18-36V DC 80W Nominal	Sector scan $\pm 180^\circ$	$\pm 20^\circ$	0.1"	Azimuth: 1 to 20 Elevation 1 to 10	RS422 (Ethernet-Optional)	0.4
PDAP-50	50	~ 26	435 x 312 x 390 (W x H x D)	24V DC 200 W Nominal	"Sector scan $\pm 180^\circ$ " Continuous 360° (optional)*	$\pm 20^\circ$	0.1"	Azimuth: 1 to 30 Elevation 1 to 15	RS422 (Ethernet-Optional)	0.5

STANDARD ACCESSORIES



Hard carrying case



Set of Cables

SPECIAL ACCESSORIES



Payload



Bracket/Adaptor





MANUAL ROTATOR/TILTER (MRT)

NAKUL SERIES

PEL's Nakul Series of Manual Rotator Tilter (MRT) is a manual Pedestal which is typically mounted on PEL's Telescopic Masts (up to 25 metres height) and provides accurate manoeuvring & alignment of Radio Antenna from the ground via a rope and pulley mechanism. It incorporates an automatic locking feature designed to prevent any movement of the payload once the ropes are not being pulled in either direction.

OUR USP'S



Rugged, compact and high reliability construction



No special tools required for Mast installation



Self locking feature prevents backlash



Operates manually in Azimuth and Elevation via ropes

MANUAL ROTATOR / TILTER (MRT)										
Model No.	Payload (Kg)	Unit Wt (Kg)	Dimintions (mm)	Power Consumption	Rotational Range	Tilt Range	Positional Accuracy	Speed (RPM)	Control Data Interface	Wind Area (m²)
MRT-25	25	15	200x 260 x 202 (W x H x D)	NA	Sector scan ± 180°	±15°	0.2°	NA	NA	0.3

STANDARD ACCESSORIES



Hard carrying case



Set of Cables

SPECIAL ACCESSORIES



Payload




Bracket/Adapter



MAJOR ACCESSORIES

MAST/ TRIPOD/ POSITIONER


Standard Accessories



Base Plate



Tilting Cup



Nails



Earthing Kit: Pipe & Cable



Lightning Arrestor



Drive On Frame



Hammer



Guy Rope



Foot Pump




Hand Held Pendant



Cable (RF, FO, Electrical, Power) Assemblies



Pneumatic Controller Unit



Pegs



Erection Stand



User Manual



Guy Rope Controller



Sand Kit

Tool Kit



DE Spanner



Adjustable Spanner



Plier (On Special Request)



Box Spanner with T Handle)



Teflon Tape



Screw Driver



Steel Oil Can




Velcro Cable Strap for Cable Tie



Levelor (Weighted Cable/ Spirit Level)



Allen Keys



Guy Marker



Nail Puller

Carrying Cases: Soft/Hard



Canvas



FRP




Roto Mould



Plastic Injection Moulding

Air Compressors



.8 Hp, Capacity 20Ltr



1 Hp, Capacity 6Ltr (Oil Free)



1 Hp, Capacity 30Ltr



1 Hp, Capacity 2Ltr (With Oil) Rugged


Vehicle Mounting Brackets



Trailer Mounting Bracket



Vehicle Roof Mount Design



Vehicle Mounting Bracket

Payload Adapter



Dual Mount



Interface Adapter



Tripods Adapter




Tripods Adapter



Dual Payload



Payload Adapter



Circular Heavy Duty Bracket



Side Mounting Payload

MULTI FUNCTION ACTIVE JUNCTION BOX

The Multi-Function Active Junction Box plays a crucial role as an essential accessory for RF, Electro-Optic, Servo-based, and Networking components. These Junction box can be installed on Towers, Telescopic Masts, Tripods, and other elevated mechanisms. Functioning as an active junction box, the PAJB facilitates effective interconnectivity for power and data interfaces.

OUR USP'S



MIL-STD design and construction



Integrated tightly to PEL tripods and masts with very economical footprint



Combination of power supply, protocol conversion and navigation



Customizable based on payload needs

Silent Features

- Customizable low foot print Junction boxes to suit every payload atop PEL Masts and Tripods
- Power Conversion and Distribution
- Provision for Battery Charging
- GNSS based direction and elevation sensing
- Various Protocol/Interface Conversion
- Media conversion RF to optical and vice versa
- Battery Power as secondary Backup



S.No.	Parameters	Specifications
1	DC Power Supply for Equipment	Input: 90 – 285V AC Output: 24V – 72V
2	Electrical Power	Up to 2 KW
3	Battery Bank	24V/ 48V/ 72V
4	Protocol Conversion	"RS232 ↔ RS422 RS232 ↔ V.35 RS232/RS422/V.35 ↔ IP"
5	Media Conversion	Electrical ↔ Optical RF ↔ Optical
6	Ethernet Switch Optical –Electrical interface	4 – 8 Ports (Electrical) 1 – 2 Ports (SFP based Optical) PoE (Optional)
7	Network Synchronization/ Home Location	Via GNSS receiver
8	Protection against Surges	Level 2
9	Protection against lightning	Level 2
10	EMI/EMC	CISPR 22/ EN5022/ MIL-STD-461
11	Environmental	Industrial (IP67)/ MIL-STD-810

POWER SOLUTIONS

Precision Electronics Limited has a long experience in delivering a wide range of power solutions for Telecom, Aerospace, Healthcare and Industrial sectors against various applications.

- Tactical AC-DC Power supplies
- Power Supplies with Battery Charger
- Power conditioning Rack (PCR)
- Power Distribution Panel (PDP)
- Customized Power Modules for Medical equipment
- Test Jigs for repair and troubleshooting


OUR USP'S



MIL-STD design and construction



Battery Charging, Power Distribution



AC-DC, DC-DC



Communications I/f's: CAN, GPIO, Serial, Ethernet

Sailent Features

- Customizable switch mode power supplies (AC-DC, DC-DC) for 300-2000W
- PFC based Battery Charger up to 3000W with built-in controller
- Power Distribution Units up to 30kVA
- Offered in high industrial (UL STD) OR MIL-STD construction
- Input Power Conditioning
- Highest operating safety
- Maximum energy efficiency



48 V SMPS (DC Power Supply)



24 V SMPS (DC Power Supply)



Battery Charger



Cable Assembly AC power



Cable Assembly DC power

S.No.	Description	SMPS-24 V (Dual O/P)	SMPS-48 V	Battery Charger
1	Input Voltage	160 to 264 V AC 50 Hz	160 to 264 V AC 50 Hz	90 to 264 V AC 50 Hz
2	Input Current	4 Amps on Full Load	4 Amps on Full Load	10 Amps on Full Load
3	Efficiency	92%	92%	94%
4	Output-1 Voltage	24 V DC Nominal (Max 30 VDC)	48 V DC Nominal (Max 54 VDC)	Nominal 51 V DC Max 58 V DC
5	Output -2 Voltage	48 V DC	N/A	N/A
6	Output Current	20 Amps @ 24 V 10 Amps @ 48 V	20 Amps	40 Amps
7	Line Regulation	2%	2%	CC and CV Mode
8	Total Power Rating	1000W	1000W	2000W
9	Cooling Methodology	Conduction Cooling	Conduction Cooling	Conduction Cooling
10	Input Protections	Over current and over voltage	Over current and over voltage	Input over current and over voltage
11	Output Protections	Over Load and over voltage	Over Load and over voltage	Batt under and over voltage Protection
12	Power Connectors	MIL C 5015 / D38999	MIL C 5015 / D38999	Type 1
13	Standards (EMI/EMC)	MIL Std 461	MIL Std 461	AIS-I38 (Part 2)
14	Standards (Environmental)	MIL Std 810/ JSS55555	MIL Std 810/ JSS55555	AIS-I38 (Part 2)
15	Dimensions	400 X 380 X 150 mm (L X W H)	360 X 370 X 170 mm (L X W H)	225 X 204 X 100 mm (L X W H)
16	Weight	7.0 Kg	8.0 Kg	5.0 Kg
17	Operating Temperature	(-20°C and +55°C)	(-20°C and +55°C)	(-10°C and +55°C)
18	Storage Temperature	(-30°C and +70°C)	(-30°C and +70°C)	(-20°C and +70°C)

Note: Specifications are subject to change without notice



HEAD OFFICE

D-10, Sector-3, Noida 201301, Uttar Pradesh, India

FOR BUSINESS ENQUIRIES

sales@pel-india.in | 0120-2551556 / 7 | Fax: 0120-2524337 | pel-india.in



FOLLOW US ON - 